




AGPS-2-2 Parallel Gripper

Single Finger, One Fixed Jaw

FEATURES AND BENEFITS



- T-Slot bearing support for the carriage and end plate offers superior load bearing performance throughout the stroke.
- Standard built-in stroke adjustment and stroke lock for precise, repetitive operation.
- Compact, lightweight unit with built-in cylinder.
- Piston seals are U-CUP type for long service life.
- Hall Effect sensors are available to monitor stroke position.
- Multiple mounting surfaces on the body and endplate with threaded and counterbored holes for easy mounting choices.
- Adjustable stroke on extend and retract.

SPECIFICATIONS

Design: Built-in air cylinder
T-slot slide

Stroke: 1 in [25.4 mm]

Thrust Force @ 80 PSI [5.5 BAR]

Extended: 35 lbs [155 N]
Retract: 33 lbs [146 N]

Recommended Speed: 2-12 in/sec [0.5-.3m/sec]

Pressure Range: Low/High 20-120 PSI [1.4-8 BAR]

Temperature Range: Low/High -20°/150°F [-28°/80°C]

Side Play: ± 0.001 [.03 mm]

Maximum Payload: 13 lbs [5.9 kg]


Material: High Strength, Aluminum Alloys, Bronze

Weight: 5.6 oz [160 g]

Piston Diameter: .750 in [19 mm]

January 2008 - PATENTED Made in the USA

MAXIMUM FORCES & MOMENTS



| | Static | Dynamic |
|-------------------|-----------------|-------------------|
| Max Tensile T | 140 lbs [622 N] | 60 lbs [266 N] |
| Max Compressive C | 140 lbs [622 N] | 60 lbs [266 N] |
| Max Moment M_x | 70 in/lb [8 Nm] | 30 in/lb [3.4 Nm] |
| Max Moment M_y | 70 in/lb [8 Nm] | 30 in/lb [3.4 Nm] |
| Max Moment M_z | 70 in/lb [8 Nm] | 30 in/lb [3.4 Nm] |

HOW TO ORDER

When ordering, please specify:
Design/Model Number and Options.

DESIGN/MODEL

- AGPS-2-1
- AGPS-2-2
- AGPS-2-3
- AGPS-2-4

METRIC

AGPS-2-2

SENSOR TYPE

- 1 = NPN
- 2 = PNP

M - 3 - 1 - 1

SENSOR OPTIONS*

- 1 = LEFT
- 2 = RIGHT
- 3 = BOTH

SENSOR CONNECTOR

- 1 = POTTED
- 2 = QUICK DISCONNECT
- 3 = QUICK DISCONNECT WITH RIGHT ANGLE

* NOTE: Hall Effect sensors are hard wired with 20" pigtail.

Sensor Part # SHN01, SHP01, SHNQ3, SHPQ3

